AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

Claims 1-16 (canceled).

Claim 17 (previously presented): A battery obtained by a method comprising the steps of:

- a) providing a composite of a solid polymer electrolyte film and a thin film-shaped porous electrode obtained by a method comprising the steps of:
 - i) providing said solid polymer electrolyte film;
- ii) providing said porous electrode comprising an electrochemically active substance;
- iii) contacting said solid polymer electrolyte film with said porous electrode; and
- iv) reducing pressure inside said porous electrode to fix said solid polymer electrolyte film to said porous electrode;
- b) superposing a second electrode on said solid polymer electrolyte film on a side opposite of said porous electrode;
- c) impregnating said porous electrode in said composite under reduced pressure with an electrolytic solution.

AMENDMENT UNDER 37 C.F.R. § 1.111 Att rney D cket No.: Q62599

U.S. Applicati n N .: 09/775,619

Claim 18 (previously presented): A battery obtained by a method comprising the

a) providing a composite of a solid polymer electrolyte film and a thin film-shaped

porous electrode obtained by a method comprising the steps of:

coating on an electrode surface of said thin film-shaped porous electrode

with a polymerizable compound which is converted to said solid polymer electrolyte or a pre-

solid polymer electrolyte upon polymerization; and

ii) reducing pressure inside said porous electrode after superposing said

electrode surface coated with said polymerization compound onto said solid polymer electrolyte

film,

steps of:

b) superposing a second electrode on said solid polymer electrolyte film on a side

opposite of said porous electrode;

i)

<u>c</u>) impregnating said porous electrode in said composite under reduced pressure

with an electrolytic solution.

Claim 19 (previously presented): The battery as claimed in claim 17, wherein said

solid polymer electrolyte film of said composite is obtained by polymerizing a composition

comprising a solvent having dissolved therein a polymerizable compound.

Claim 20 (previously presented): The battery as claimed in claim 18, wherein said solid

3

Att rney D cket N .: Q62599

AMENDMENT UNDER 37 C.F.R. § 1.111 U.S. Applicati n N .: 09/775,619

polymer electrolyte film of said composite is obtained by polymerizing a composition comprising a solvent having dissolved therein a polymerizable compound.

Claim 21 (previously presented): The battery as claimed in claim 17, wherein said polymer electrolyte film has an ion conductivity at room temperature of 10^{-5} S/cm or more.

Claim 22 (previously presented): The battery as claimed in claim 18, wherein said polymer electrolyte film has an ion conductivity at room temperature of 10^{-5} S/cm or more.

Claim 23 (previously presented): The battery as claimed in claim 17, wherein said solid polymer electrolyte film contains a cross-linking polymer having a urethane bond and an oxyalkylene group.

Claim 24 (previously presented): The battery as claimed in claim 18, wherein said solid polymer electrolyte film contains a cross-linking polymer having a urethane bond and an oxyalkylene group.

Claim 25 (previously presented): The battery as claimed in claim 18, wherein said polymerizable compound coated on said porous electrode has a urethane bond and oxyalkylene group.

Claim 26 (previously presented): A battery according to claim 19, wherein said solid polymer electrolyte film contains no electrolyte salt.

Claim 27 (previously presented): A battery according to claim 20, wherein said solid polymer electrolyte film contains no electrolyte salt.

Claim 28 (previously presented): The battery according to claim 26, wherein said electrolytic solution comprises a polymerizable compound and an electrolyte salt and said polymerizable compound is polymerized to cure after impregnation under reduced pressure.

Claim 29 (previously presented): The battery according to claim 27, wherein said electrolytic solution comprises a polymerizable compound and an electrolyte salt and said polymerizable compound is polymerized to cure after impregnation under reduced pressure.

Claim 30 (currently amended): A battery obtained by a method comprising the steps of:

- a) providing a composite of a solid polymer electrolyte film and a thin film-porous electrode obtained by a method comprising the steps of:
 - providing said solid polymer electrolyte film;
 - ii) providing said porous electrode comprising an electrochemically active

AMENDMENT UNDER 37 C.F.R. § 1.111 Attorney D cket N .: Q62599

U.S. Application N .: 09/775,619

substance;

iii) contacting said solid polymer electrolyte film with said porous electrode;

and

iv) reducing pressure inside said porous electrode to fix said solid polymer

electrolyte film to said porous electrode;

b) superposing a second electrode on said solid polymer electrolyte film on a side

opposite of said porous electrode;

c) impregnating said porous electrode of said composite with an electrolytic solution

which has a concentration of an electrolyte salt greater than a concentration at which the

electrolytic solution has a maximum ion conductivity,

wherein said solid polymer electrolyte film of said composite is obtained by polymerizing

a composition comprising a solvent having dissolved therein a polymerizable compound and

contains no salt.

Claim 31 (currently amended): A battery obtained by a method comprising the steps

of:

a) providing a composite of a solid polymer electrolyte film and a thin film-porous

electrode obtained by a method comprising the steps of:

i) coating on an electrode surface of said porous electrode with a

polymerizable compound which is converted to said solid polymer electrolyte or a pre-solid

6

AMENDMENT UNDER 37 C.F.R. § 1.111 Attorney D cket N .: Q62599

U.S. Applicati n N .: 09/775,619

polymer electrolyte upon polymerization; and

ii) reducing pressure inside said porous electrode after superposing said

electrode surface coated with said polymerization compound onto said solid polymer electrolyte

film;

b) superposing a second electrode on said solid polymer electrolyte film on a side

opposite of said porous electrode;

c) impregnating said porous electrode of said composite with an electrolytic solution

which has a concentration of an electrolyte salt greater than a concentration at which the

electrolytic solution has a maximum ion conductivity,

wherein said solid polymer electrolyte film of said composite is obtained by polymerizing

a composition comprising a solvent having dissolved therein a polymerizable compound and

contains no salt.

Claim 32 (previously presented): The battery according to claim 30, wherein said

electrolytic solution comprises a polymerizable compound and an electrolyte salt and said

polymerizable compound is polymerized to cure after impregnation under reduced pressure.

Claim 33 (previously presented): The battery according to claim 31, wherein the

electrolytic solution comprises a polymerizable compound and an electrolyte salt and the

polymerizable compound is polymerized to cure after the impregnation under reduced pressure.

7